

PATENT ABSTRACTS OF JAPAN

(11)Publication number : **2004-023145**

(43)Date of publication of application : **22.01.2004**

(51)Int.Cl.

H04L 1/00

H04B 7/26

(21)Application number : **2002-171435**

(71)Applicant : **MITSUBISHI ELECTRIC CORP**

(22)Date of filing : **12.06.2002**

(72)Inventor : **YAMAUCHI NAOHISA
SHIBUYA AKIHIRO**


(54) **MOBILE COMMUNICATION SYSTEM AND ADAPTIVE MODULATION METHOD**

(57)Abstract:

PROBLEM TO BE SOLVED: To provide a mobile communication system and an adaptive modulation method capable of adaptively changing each of modulation methods and each of Error Correction Coding methods by quickly reflecting the line quality estimated at a mobile station in selecting one of the modulation methods and one of the Error Correction Coding methods.

SOLUTION: As a threshold for changing adaptive modulation levels each having a different transmission rate in response to the line quality by combining the modulation methods and the Error Correction Coding methods, a threshold table 73 is provided with a referential threshold table, a low threshold table having lower threshold level than that of the referential threshold table by a predetermined level, and a high threshold table having higher threshold level than that of the referential threshold table by a predetermined level.

An adaptive modulation management unit 71 is designed to determine whether or not to request for changing selected adaptive modulation level by using the low threshold table when the adaptive modulation level is to be lowered again after having been lifted, and to determine whether or not to request for changing the selected adaptive modulation level by using the high threshold table when the adaptive modulation level is to be lifted again after having been lowered.



(19) 日本国特許庁(JP)

(12) 公開特許公報(A)

(11) 特許出願公開番号

特開2004-23145

(P2004-23145A)

(43) 公開日 平成16年1月22日(2004.1.22)

(51) Int.Cl.⁷

H04L 1/00

H04B 7/26

F 1

H04L 1/00

H04B 7/26

E

M

テーマコード(参考)

5K014

5K067

審査請求 未請求 請求項の数 10 O L (全 30 頁)

(21) 出願番号 特願2002-171435 (P2002-171435)

(22) 出願日 平成14年6月12日 (2002.6.12)

(71) 出願人 000006013

三菱電機株式会社

東京都千代田区丸の内二丁目2番3号

(74) 代理人 100089118

弁理士 酒井 宏明

(72) 発明者 山内 尚久

東京都千代田区丸の内二丁目2番3号 三

菱電機株式会社内

(72) 発明者 渋谷 昭宏

東京都千代田区丸の内二丁目2番3号 三


菱電機株式会社内


Fターム(参考) 5K014 AA01 DA02 EA08 FA11 GA01

5K067 AA02 AA23 BB21 DD11 EE02

EE10 HH01 HH22 HH23 HH25

(54) 【発明の名称】 移動通信システムおよび適応変調方法





適応変調方式レベル (MCS)	変調方式	誤り訂正符号化率
MCS1	QPSK	1/2
MCS2	QPSK	3/4
MCS3	16QAM	1/2
MCS4	16QAM	3/4

MCS	閾値 (SNR)	
	所要FER=10E-1	所要FER=10E-2
1		
2	$\geq +3\text{dB}$	$\geq +10\text{dB}$
3	$\geq +6\text{dB}$	$\geq +13\text{dB}$
4	$\geq +9\text{dB}$	$\geq +16\text{dB}$

MCS	閾値 (SNR)	
	所要FER=10E-1	所要FER=10E-2
1		
2	$\geq +2\text{dB}$	$\geq +9\text{dB}$
3	$\geq +5\text{dB}$	$\geq +12\text{dB}$
4	$\geq +8\text{dB}$	$\geq +15\text{dB}$

MCS	閾値 (SNR)	
	所要FER=10E-1	所要FER=10E-2
1		
2	$\geq +4\text{dB}$	$\geq +11\text{dB}$
3	$\geq +7\text{dB}$	$\geq +14\text{dB}$
4	$\geq +10\text{dB}$	$\geq +17\text{dB}$

